

## Twin Boiler Dryer



### Twin Boiler Dryer Model GC-QL-II for Higher Moisture Content 20-50%

Model	GC-QL-II-7.5	GC-QL-II-11	GC-QL-II-15
Capacity(Kg/hour)	400-500KG	500-700KG	900-1000KG
Size of Input Material (Diameter)	< 3mm & < 5mm	< 3mm & < 5mm	< 3mm & < 5mm
Temperature of Hot Air	180°C~250°C	180°C~250°C	180°C~250°C
Consumption of Wood Waste	60kg/h	100kg/h	150kg/h
Moister content max %	20-50%	20-50%	20-50%
Moisture of material after drying	8-12%	8-12%	8-12%
Power (Air Fan+Air Lock+ speed adjustable feed motor)	7.5kw+0.75kw +0.75kw	11kw+0.75kw +0.75kw	15kw+0.75kw+0.75kw
Net/Gross Weight	2040/2260kg	2850/3080kg	2850/3080kg
Overall dimension(L*W*H)	9m*2.4m*4m	9m*3.2m*4m	9.5m*3.8m*4.5m
Packing size	11 M3(3 cases)	14 M3(3 cases)	18 M3(3 cases)

**[Contact Us for Details >>](#)**

**COMPANY NAME:** Anyang General International Co., Ltd

**ADDRESS:** Suite A, 4/F, Jinhao Business Bld., Renmin Rd. Anyang, Henan, P.R.C.

**PC:** 455000

**TEL:** (86) 372 5965148

**FAX:** (86) 372 5951936

**E-MAIL:** [info@briquette-machine.com](mailto:info@briquette-machine.com)

**AGICO GROUP**

Briquetting Equipment Manufacturer & Supplier

**TEL:** (86) 372 5965148

**FAX:** (86) 372 5951936